

Maverick Series

If you're looking for a hot water unit with large volume capacity, look no further. The **Maverick Series** works great in industrial applications requiring 20 or more hours of use per week and is built for longevity. The top-fired heat exchanger is energy efficient and designed for convenient troubleshooting.

Electric Direct Drive

- Energy-efficient top-fired heat exchanger designed for convenient troubleshooting and easy maintenance



1000 to 2000 psi

Electric Belt Drive

- Energy-efficient top-fired heat exchanger designed for convenient troubleshooting and easy maintenance
- Heavy-duty dual cogged belt drive system to prevent slippage



2500 to 3500 psi

Additional Features:

Pump

- Direct or belt drive triplex piston General or Mi-T-M pump with ceramic plungers
- Stainless-steel and brass unloader valve
- Forged brass manifold
- Thermal relief valve
- High pressure detergent injector (available as an option on OMM11 models)

Motor

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 35-foot power cord with in-line GFCI which meets required CSA certification (GFCI not available on 3000 and 3500-PSI models)
- Solid state electronic ignition

Components

- Float tank (not available on OMM11 models)
- Pressure and high limit safety controls
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- Polyethylene burner fuel tank
- High quality fuel filter/water separator ensures clean fuel supply
- Easy coil drain helps prevent freezing in cold weather

Frame

- Reinforced powder coated steel tube frame with center balanced lifting hook
- Powder coated steel hose reel mounting bracket (belt drive models)
- Electric cord hanger
- Powder coated steel gun/wand holder
- Solid steel threaded axles (2500-3000-PSI models)
- Locking tire brake
- Flat-free tires

Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F
- Water output temperature is 190°-200°F

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° & 40°
- 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off