

# Alklean Gasoline Silver Series



The *Gasoline Engine Silver Series* is a compact versatile machine, with a fold down handle and optional wheel kit, this machine fits through a 30-inch doorway.

The *Silver Belt Series* is a small, compact mini skid that installs easily in tight spaces.

## Gasoline Direct Drive

- Compact design, fits through a 30-inch doorway
- 12V burner with fuel/water separator  
(Battery not included)
- Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil
- Stainless-steel removable panel



(shown with optional hour meter)

3500 or 3800 psi.

### Silver Direct Drive Series

#### Additional Features: Pump

- Direct drive triplex piston AR pump
- Forged brass manifold
- Thermal relief valve

#### Engine

- Performance-proven engine

#### Frame

- Heavy-duty powder coated steel square tube frame

#### Components

- No.1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)

#### Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F
- Adjustable thermostat

#### Unit Includes:

- Low pressure detergent injector
- Quick connect nozzles – 0°, 15°, 25° & 40°
- 50-foot x 3/8-inch high pressure hose with quick connects
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance

## Gasoline - Belt Drive

- 12V burner with fuel/water separator  
(Battery not included)
- Stainless-steel control panel with optional steam, high pressure chemical and thermostat
- Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil



3000 psi.

(shown with optional steam and hour meter)

### Silver Belt Drive Series

#### Additional Features: Pump

- Belt drive triplex piston General pump
- Forged brass manifold
- Thermal relief valve

#### Engine

- Performance-proven gasoline engine or Kohler diesel engine

#### Frame

- Heavy-duty powder coated steel square tube frame

#### Components

- No.1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)

#### Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F
- Adjustable thermostat

#### Unit Includes:

- Low pressure detergent injector
- Quick connect nozzles – 0°, 15°, 25° & 40°
- 50-foot x 3/8 inch high pressure hose with quick connects
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance