

Alklean O-F Series



Designed, manufactured and tested in the tradition of quality, this stationary diesel powered hot water pressure washer is the perfect choice for any efficient wash bay set-up.

2000 to 3000 psi
4.8 to 3.9 gpm
Many Options Available

Electric Powered Oil-Heated Belt Drive

- Beckett burner with fuel/water separator
- Belt drive triplex piston General pump with ceramic plungers
- 10-inch draft diverter
- 1/2-inch schedule 80-coil with 5 pancake heat exchanger
- High pressure outlet hose connection
- Adjustable thermostat
- On/Off pump/motor switch
- On/Off burner switch



(shown with optional fuel tanks,)



(shown with panels off)

Additional Features:

Pump

- Thermal relief valve
- Factory preset trapping unloader

Motor

- Single or three-phase open drip-proof electric motor with thermal overload protection

Frame

- Powder coated steel frame with removable side panels

Components

- Polyethylene float tank (4-gallon with in-line screen filter)
- 24V control system

Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F (250°F/121°C outlet temperature with steam option)
- Designed to run off an existing fuel tank (optional fuel tanks available)

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° & 40°
- 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance with fixed detergent nozzle