

MATERIAL SAFETY DATA SHEET – Bandit-200

Manufactured by: Alklean Industries, Inc.
2111 Catalina
Pasadena, TX 77503

Telephone #: 281-479-5966
Toll free #: 800-458-6304
Date Prepared: 03-27-03

SECTION I – PRODUCT IDENTIFICATION

Product Name: Bandit-200
Synonyms:
Chemical Description:
Intended Use: Vehicle and General Purpose Industrial Cleaner

SECTION II – HAZARDOUS INGREDIENTS

Chemical ID	CAS Number	% Weight	OSHA PEL	ACGIH TLV
Sodium Hydroxide		1%		

SECTION III – PHYSICAL & CHEMICAL PROPERTIES

Appearance and Odor: Purple Liquid with Aromatic Odor	pH: 12.5
Boiling Point °F/C: 220F	Specific Gravity (Water=1): 1.12
Vapor Pressure (mm Hg): 23.76 @ 25°C	Melting Point (°F/C): Undet.
Vapor Density (Air=1):	Evaporation Rate (Butyl Acetate=1):
Solubility in Water: 100%	

SECTION IV – FIRE AND EXPLOSION HAZARD

Flash Point (Method): >220°F Flammable Limits (LFL/UFL):
Extinguishing Media: Water, Carbon Dioxide, Foam
Special Fire Fighting Procedures: None
Fire and Explosion Hazards: Non-Flammable

SECTION V – HEALTH HAZARD AND FIRST AID

Routes of Entry (Inhale, Ingest, Skin, Eye): All
Health Hazard (Acute and Chronic): Eye and skin irritation
Carcinogen/Details: No
OSHA Regulated?
Signs and Symptoms of Exposure: See "Health Hazard" above
Medical Conditions Generally Aggravated by Exposure:
Emergency and First Aid Procedures: Inhalation - Move to fresh air.
Ingestion - Drink milk or water in large amounts and get medical attention.
Skin - Wash with soap and water.
Eyes - Flush with water for 15 minutes and seek medical attention.

SECTION VI – STABILITY AND REACTIVITY

Stability: Stable Conditions to Avoid: None known
Incompatibles: None known
Hazardous Decomposition:
Hazardous Polymerization: Will Not Occur Conditions to Avoid:

