

Alklean Platinum Series Diesel Engine

Designed with professional contract cleaners in mind, the *Platinum Series* is perfect for the heaviest construction applications, and durable enough to handle 24-hours-a-day, seven-days-a-week run-time.



- Three-way ball valve for inlet water selection
- Control panel includes 120V/15-amp auxiliary switch for a duplex GFCI outlet
- Stainless-steel coil wrap and control panel prevents rust
- Stainless-steel removable front panel for access to pump
- 25° nozzle for wet steam operation



ALKLEAN
INDUSTRIES, INC.

"ALWAYS CLEAN . . . ALWAYS ALKLEAN"

3000 to 4000 psi.

- Detergent valve
- Hour meter
- Adjustable temperature control
- Auxiliary power switch

Additional Features:

Pump

- Belt drive triplex piston General pump

Engine

- liquid-cooled Kubota diesel engine

Components

- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- High quality fuel filter/water separator ensures clean fuel supply
- Pressure switch and thermal relief valve safety controls

Frame

- Heavy-duty powder coated steel frame

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° & 40°
- 50-foot x 3/8 inch steel wire-braided pressure hose with quick connects (1/2-inch on HDS-3008 models)
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance with fixed detergent nozzle
- Adjustable high pressure detergent injector