

Alklean ALL ELECTRIC Series



The new all-electric belt drive pressure washer comes standard with heat exchanger cartridges that provide consistent and efficient on-demand hot water.



Patent Pending

Pump

- Belt drive triplex piston General pump
- Stainless-steel and brass unloader valve
- Forged brass manifold
- Thermal relief valve

Motor

- Industrial 6.0 or 8.0-HP electric motor
- Hard-wired to heat exchanger
- On/Off power switch

Frame

- Stainless-steel base and frame with rubber isolators

Component

- Time delay shutdown

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° & 40°
- External downstream detergent injector, AW-8400-0021, with detergent nozzle
- 50-foot x 3/8-inch high pressure black hose with quick connects, 5800-PSI rated, R2
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated lance

Heat Exchanger

- Used for consistent and efficient on-demand hot water
- 120°F to 130°F temperature rise above in-take water, obtained within 3 to 5 minutes
- Adjustable thermostat
- On/Off power switch
- Powder coated steel frame
- Revolutionary cartridge design
- Low maintenance, stainless-steel coils in aluminum casings for maximum efficiencies
- Eliminates constant cleaning
- Eliminates heat loss



Model Number	PSI	GPM	Horsepower/Motor	Unit Amperage	Pump	Unloader	Heater kW	Temperature Rise	Dimensions (LxWxH)	Ship Wt.	Net Wt.
ALK-2503	2500	2.8	6.0 HP, 460V, 3Ø	66.0A	General	Factory preset	48	120°F	36x25x49in.	725 lb.	625 lb.
ALK-3004	3000	3.9	8.0 HP, 460V, 3Ø	98.0A	General	Factory preset	72	130°F	36x25x49in.	830 lb.	725 lb.

Options:		
Part Number	Description	Fits Models
	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	All models
	Remote box - Adds control box which may be mounted away from unit to control on/off	All models