

# Alklean **Roughneck** Series



The **Roughneck** Series offers portability and reliability suitable for the most rugged applications.

## Electric Powered Oil-Heated Belt Drive

1000 to 3000 psi

- Auto start/stop
- Time delay shutdown
- Belt drive triplex AR or General plunger pump
- 13-inch flat-free tires with rear tire brake
- Stainless-steel coil wrap
- Horizontal schedule 80 pipe coil



### **Additional Features:**

#### **Pump**

- Triplex piston pump with ceramic plungers

#### **Motor**

- Open drip-proof electric motor with thermal overload protection
- 35-foot power cord (GFCI with 20-amp plug on 1.5 to 6.0 HP, 1Ø models except on 208V, 1Ø models)

#### **Frame**

- Wrinkle-finish powder coated steel frame assembly
- Wand holder

#### **Components**

- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Pressure switch and high limit safety controls
- On/Off pump/motor switch

- On/Off burner switch
- Hour meter
- Adjustable thermostat
- Polyethylene float tank with inlet filter screen
- Adjustable pressure detergent injector

#### **Miscellaneous**

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

#### **Unit Includes:**

- Quick connect nozzles – 0°, 15°, 25°, 40° and low pressure nozzle
- 50-foot x 3/8-inch high pressure hose with quick connects
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off